

CSci 223, Spring 2005
Homework #4: Defusing a Binary Bomb
Due: Monday, April 25th, 11:00am

1 Introduction

The nefarious *Dr. Evil* has planted a slew of “binary bombs” on our machines. A binary bomb is a program that consists of a sequence of phases. Each phase expects you to type a particular string on *stdin*. If you type the correct string, then the phase is *defused* and the bomb proceeds to the next phase. Otherwise, the bomb *explodes* by printing "BOOM!!!" and then terminating. The bomb is defused when every phase has been defused.

There are too many bombs for us to deal with, so we are giving each group a bomb to defuse. Your mission, which you have no choice but to accept, is to defuse your bomb before the due date. Good luck, and welcome to the bomb squad!

Step 1: Get Your Bomb

Each group of students will attempt to defuse their own personalized bomb. Each bomb is a Linux binary executable file that has been compiled from a C program. To obtain your group’s bomb, one (and only one) of the group members should point your Web browser to the bomb request daemon at

`http://onyx.cs.olemiss.edu:15213`

Fill out the HTML form with the email addresses and names of your team members, and then submit the form by clicking the “Submit” button. The request daemon will build your bomb and return it immediately to your browser in a `tar` file called `bombk.tar`, where k is the unique number of your bomb.

Save the `bombk.tar` file to a (protected) directory on `onyx` in which you plan to do your work. Then give the command: `tar xvf bombk.tar`. This will create a directory called `./bombk` with the following files:

- `README`: Identifies the bomb and its owners.
- `bomb`: The executable binary bomb.

- `bomb.c`: Source file with the bomb's main routine.

If you change groups, simply request another bomb and we'll sort out the duplicate assignments later on when we grade the lab.

Also, if you make any kind of mistake requesting a bomb (such as neglecting to save it or typing the wrong group members), simply request another bomb.

Step 2: Defuse Your Bomb

Your job is to defuse the bomb.

You can use many tools to help you with this; please look at the **hints** section for some tips and ideas. The best way is to use your favorite debugger to step through the disassembled binary.

Each time your bomb explodes it notifies your instructor, and you lose 1 point in the final score for the assignment. So there are consequences to exploding the bomb. You must be careful!

The first phase is worth 30 points. The second is worth 45 points. The third is worth 25 points. The fourth and fifth phases are worth 10 points of extra credit each. The sixth phase is worth 20 points of extra credit. There are 140 possible points. This is an excellent chance for some of you to catch up.

The phases get progressively harder to defuse, but the expertise you gain as you move from phase to phase should offset this difficulty. However, the last phase will challenge even the best students, so please don't wait until the last minute to start.

The bomb ignores blank input lines. If you run your bomb with a command line argument, for example,

```
linux> ./bomb psol.txt
```

then it will read the input lines from `psol.txt` until it reaches EOF (end of file), and then switch over to `stdin`. In a moment of weakness, Dr. Evil added this feature so you don't have to keep retyping the solutions to phases you have already defused.

To avoid accidentally detonating the bomb, you will need to learn how to single-step through the assembly code and how to set breakpoints. You will also need to learn how to inspect both the registers and the memory states. One of the nice side-effects of doing the lab is that you will get very good at using a debugger. This is a crucial skill that will pay big dividends the rest of your career.

Logistics

You may work in a group of up to 2 people.

Any clarifications and revisions to the assignment will be posted on the class bboard and Web page.

You should do the assignment on `onyx`. In fact, there is a rumor that Dr. Evil really is evil, and the bomb will always blow up if run elsewhere. There are several other tamper-proofing devices built into the bomb as well, or so they say.

Hand-In

There is no explicit hand-in. The bomb will notify your instructor automatically after you have successfully defused it. You can keep track of how you (and the other groups) are doing by looking at

<http://onyx.cs.olemiss.edu/~bomb/csci223-spring2005.html>

This web page is updated continuously to show the progress of each group.

Hints (*Please read this!*)

There are many ways of defusing your bomb. You can examine it in great detail without ever running the program, and figure out exactly what it does. This is a useful technique, but it not always easy to do. You can also run it under a debugger, watch what it does step by step, and use this information to defuse it. This is probably the fastest way of defusing it.

We do make one request, *please do not use brute force!* You could write a program that will try every possible key to find the right one. But this is no good for several reasons:

- You lose 1/4 point (up to a max of 10 points) every time you guess incorrectly and the bomb explodes.
- Every time you guess wrong, a message is sent to the staff. You could very quickly saturate the network with these messages, and cause the system administrators to revoke your computer access.
- We haven't told you how long the strings are, nor have we told you what characters are in them. Even if you made the (wrong) assumptions that they all are less than 80 characters long and only contain letters, then you will have 26^{80} guesses for each phase. This will take a very long time to run, and you will not get the answer before the assignment is due.

There are many tools which are designed to help you figure out both how programs work, and what is wrong when they don't work. Here is a list of some of the tools you may find useful in analyzing your bomb, and hints on how to use them.

- gdb

The GNU debugger, this is a command line debugger tool available on virtually every platform. You can trace through a program line by line, examine memory and registers, look at both the source code and assembly code (we are not giving you the source code for most of your bomb), set breakpoints, set memory watch points, and write scripts. Here are some tips for using gdb.

- To keep the bomb from blowing up every time you type in a wrong input, you'll want to learn how to set breakpoints.
- The CS:APP Student Site at <http://csapp.cs.cmu.edu/public/students.html> has a very handy single-page gdb summary.

– For other documentation, type “help” at the gdb command prompt, or type “man gdb”, or “info gdb” at a Unix prompt. Some people also like to run gdb under gdb-mode in emacs.

- `objdump -t`

This will print out the bomb’s symbol table. The symbol table includes the names of all functions and global variables in the bomb, the names of all the functions the bomb calls, and their addresses. You may learn something by looking at the function names!

- `objdump -d`

Use this to disassemble all of the code in the bomb. You can also just look at individual functions. Reading the assembler code can tell you how the bomb works.

Although `objdump -d` gives you a lot of information, it doesn’t tell you the whole story. Calls to system-level functions are displayed in a cryptic form. For example, a call to `sscanf` might appear as:

```
8048c36: e8 99 fc ff ff  call  80488d4 <_init+0x1a0>
```

To determine that the call was to `sscanf`, you would need to disassemble within `gdb`.

- `strings`

This utility will display the printable strings in your bomb.

Looking for a particular tool? How about documentation? Don’t forget, the commands `apropos` and `man` are your friends. In particular, `man ascii` might come in useful. Also, the web may also be a treasure trove of information. If you get stumped, feel free to ask your TA for help.